



SLOT WEDGE DMD 3-PLY-LAMINATE (WHITE) CLASS F 155°C. THICKNESS 0.36 – 0.46 MM



Slot wedge with high dielectric strength and good mechanical and thermal properties. The prestressed profile warrants very high rigidity and stability and contributes to a fast, safe installation

- Working temperature +155°C
- Thickness 0.36 – 0.46 mm



PRODUCT INFORMATION

Slot wedge DMD 3-ply-laminate, polyester fiber / polyester film / polyester fiber with high dielectric strength and good mechanical properties

Typical applications

Suitable for winding applications

Properties

- Good mechanical properties
- Adapted for Class F varnishes
- Good electrical properties

Composition

• 3-ply laminate, polyester fiber/polyester film/polyester fiber impregnated with high temperature resin

Colour

- White

Packaging

- Bundles of 100 metres
- Length 1000 mm

Technical data


- Temperature Class F 155°C
- Dielectric strength
- 0.36 mm \geq 20 kV
- 0.46 mm \geq 24 kV
- Thickness tolerance \pm 15%

Product information for which Carbex bears no responsibility is provided by the manufacturer. 2017-04-04





SLOT WEDGE DMD 3-PLY-LAMINATE (WHITE) CLASS F 155°C. THICKNESS 0.36 – 0.46 MM



ITEM NUMBER	TYPE B	DIMENSIONS mm	PACK-AGING	DIELECTRIC STRENGTH KV	TENSILE STRENGTH N/mm ²	WEIGHT g/m ²	THICKNESS FILM μm
03 024 0112	SPÅRL DMD 11 x 2	11 x 2 x 0.36 x 1000	100 m	≥ 20	≥ 110	435	250
03 024 0123	SPÅRL DMD 12 x 3	12 x 3 x 0.36 x 1000	100 m	≥ 20	≥ 110	435	250
03 024 0133	SPÅRL DMD 13 x 3,5	13 x 3.5 x 0.36 x 1000	100 m	≥ 20	≥ 110	435	250
03 024 0144	SPÅRL DMD 14 x 4	14 x 4 x 0.36 x 1000	100 m	≥ 20	≥ 110	435	250
03 024 0165	SPÅRL DMD 16 x 5	16 x 5 x 0.36 x 1000	100 m	≥ 20	≥ 110	435	250
03 024 0186	SPÅRL DMD 18 x 6	18 x 6 x 0.36 x 1000	100 m	≥ 24	≥ 100	570	350
03 024 0207	SPÅRL DMD 20 x 7	20 x 7 x 0.46 x 1000	100 m	≥ 24	≥ 100	570	350
03 024 0228	SPÅRL DMD 22 x 8	22 x 8 x 0.46 x 1000	100 m	≥ 24	≥ 100	570	350
03 024 0249	SPÅRL DMD 24 x 9	24 x 9 x 0.46 x 1000	100 m	≥ 24	≥ 100	570	350
03 024 2610	SPÅRL DMD 26 x 10	26 x 10 x 0.46 x 1000	100 m	≥ 24	≥ 100	570	350
03 024 2812	SPÅRL DMD 28 x 12	28 x 12 x 0.45 x 1000	100 m	≥ 24	≥ 100	570	350

Product information for which Carbex bears no responsibility is provided by the manufacturer. 2017-04-04

